

TECHNISCHE DATEN SPECIFICATIONS		HOLZ / WOOD	STEIN / STONE
Format Size		1524 x 228 mm	935 x 465 mm
Stärke Thickness		6,5 mm	6,5 mm
Vinyl- inkl. Nutzschrift Wear layer		1,2/0,55 mm	1,2/0,55 mm
Vergütung Coating		UV	UV
Struktur Surface		Relief	Travertin
Gefaste Kanten Bevelled edge		Nein No	Nein No
Verbindung Connection		Uniclic	Uniclic
Verlegung Laying		Schwimmende Floating	Schwimmende Floating
1 Karton Box	Stück Pieces	5	4
	m ²	1,737	1,739
	Kg	19,5	17,4
1 Palette Pallet	Kartons Boxes	36	36
	m ²	62,532	62,604
	Kg Netto net	702	626
Rutschhemmstufe Antislip category	DIN 51130	R9	R9
Rutschfestigkeitsklasse Slip resistance class	EN 14041	DS	DS
Resteindruck Residual indentation	EN 433	Erfüllt Pass	Erfüllt Pass
Chemikalienbeständigkeit Chemical resistance	EN 423	Gut Good	Gut Good
Trittschallreduktion Sound reduction	ISO 140-8	18 dB	18 db
Verschleissverhalten Wear resistance	EN 660-2	Gr. T	Gr. T
Brandverhalten Flammability	BS EN 13501	B _{fl} -s1	B _{fl} -s1
Formaldehyd Formaldehyde		E1	E1
Fussbodenheizung Underflooring heating	EN 649	Geeignet für Fussbodenheizung Suitable for floor heating	
Nutzungs-kategorie Utilization class		32	32
Garantie Warranty	Wohnen Residential Gewerblich gering Light commercial	5 Jahre Years 3 Jahre Years	5 Jahre Years 3 Jahre Years



Produced under license of Unilin - EP nr. 0843763/U.S. patent nr. 6,006,486

